


RevNo	Revision note	Date	Signature	Checked
00	Sketch Only			



Material & Finishing:

1. Center conductor: Beryllium copper, Gold Plating
2. Insulators: PTFE
3. Body : Brass, Ternary Alloy Plating
4. Other Metal Parts:Crimp Ferrule:Brass,Nickel Plating

Electrical Data:

1. Impedance: 50 Ohms
2. Frequency: 0~6GHz
3. VSWR: $\leq 1.15(0\sim 3\text{GHz})$

RoHS Compliant.

UNLESS OTHERWISE NOTED ALL SURFACES FINISHED TO 64 MAX.		
ALL TOLERANCES ARE:		
DECIMALS	FRACTIONS	ANGLES
$x \pm 1.0$	$\pm 1/64$	$x' \pm 1'$
$x.x \pm 0.5$		$x'x' \pm 0.5'$
	$x.xx \pm 0.1$	



THESE DRAWING & SPEC. ARE THE PROPERTY OF LEILUO RF AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT.

ALL DIMENSIONS ARE IN MILLIMETERS AND [INCHES]

Unit:mm

Title SMA Female Crimp for LMR300 Cable			
Drawn by	Ckd by	Appd by	Date
Scale 5:1	Sheet 1 of 1	3660883	