

	A	B	C	D	E	F
RevNo	Revision note			Date	Signature	Checked
00	Sketch Only					
4						
3						
2	Material & Finishing: 1. Center conductor:Phosphor Bronze ,Silver Plating 2. Insulators: PTFE 3. Body : Brass, Ternary alloy Plating 4. Other Metal Parts: Brass,Ternary alloy Plating 5. Gasket: Silicone Rubber Electrical Data: 1. Impedance: 50 Ohms 2. Frequency: 0~6GHz 3. VSWR: ≤1.15(0~3GHz) 4. Test Voltage: 1000V rms 5. Work Voltage: 480V rms 6. Insulation Resistance: ≥5000MΩ					
1	RoHS Compliant. UNLESS OTHERWISE NOTED ALL SURFACES FINISHED TO 64/MAX. ALL TOLERANCES ARE: DECIMALS FRACTIONS ANGLES x ± 1.0 ±1/64 x' ± 1° x.x ± 0.5 x.xx ± 0.1 x'x' ± 0.5 THESE DRAWING & SPEC. ARE THE PROPERTY OF LEILUO RF AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT THEIR EXPRESS WRITTEN CONSENT. ALL DIMENSIONS ARE IN MILLIMETERS AND [INCHES] Unit:mm Title SMA Male Solder for RG141 Cable Drawn by Checked by Appd by Date Scale 5:1 Sheet 1 of 1					
	A	B	C	D	E	F